

Nové datasheety:

[JMAX2077](#) - Octal-Channel Ultrasound Front-End

[MAX3799](#) - 1Gbps to 14Gbps, SFP+ Multirate Limiting Amplifier and VCSEL Driver

[MAX17126](#) - Multi-Output Power Supply with VCOM Amplifier and High-Voltage Gamma Reference for LCD TVs

[MAX9820](#) - DirectDrive Headphone Amplifier with External Gain

[MAX14523A](#), [MAX14523AL](#), [MAX14523B](#), [MAX14523C](#) - 250mA to 1.5A, Adjustable Current-Limit Switches

[MAX3679A](#) - +3.3V, Low-Jitter Crystal to LVPECL Clock Generator

[MAX1438B](#) - Octal, 12-Bit, 64Msps, 1.8V ADC with Serial LVDS Outputs

[MAX16056](#), [MAX16057](#), [MAX16058](#), [MAX16059](#) - 125nA Supervisory Circuits with Capacitor-Adjustable Reset and Watchdog Timeouts

[MAX2164](#) - ISDB-T 1-Segment Tuner

Upravené datasheety:

[MAX6495](#), [MAX6496](#), [MAX6497](#), [MAX6498](#), [MAX6499](#) - 72V, Overvoltage-Protection Switches/Limiter Controllers with an External MOSFET

[MAX16800](#) - High-Voltage, 350mA, Adjustable Linear High-Brightness LED (HB LED) Driver

[MAX6730](#), [MAX6731](#), [MAX6732](#), [MAX6733](#), [MAX6734](#), [MAX6735](#) - Single-/Dual-/Triple-Voltage μ P Supervisory Circuits with Independent Watchdog Output

[DS2784](#) - 1-Cell Stand-Alone Fuel Gauge IC with Li+ Protector and SHA-1 Authentication

Application Notes:

[FAQs](#) [about](#) [Interface](#), [RS-232](#), [and](#) [RS-485](#) [Circuits](#) -

[ehshtml=http://www.maxim-ic.com/appnotes.cfm/an_pk/4562]Náhľad[ehshtml]