



Obsah:

Conversions	
Physical constants	
Standard decimal prefixes	
Metric conversions	
Temperature conversions	
Error conversions (ppm)	
Discrete components	
Resistor color code	
Standard resistor values	
Practical capacitor models	
Practical capacitors vs. dielectric materials	
Capacitor type overview	
Standard capacitance values	
Capacitance marking and tolerance	
Diodes and LEDs	
Analog	
Capacitor equations (series, parallel, charge, energy)	
Inductor equations (series, parallel, energy)	
Capacitor charge and discharge	
RMS and mean voltage definition	
RMS and mean voltage examples	
Logarithmic mathematical definitions	
dB definitions	
Log scale	
Pole and zero definitions and examples	
Time to phase shift	
Amplifier	
Basic op amp configurations	
Op amp bandwidth	
Full power bandwidth	
Small signal step response	
Noise equations	
Phase margin	
Stability open loop SPICE analysis	
Instrumentation Amp filter	
PCB and wire	
PCB conductor spacing	
Self-heating of PCB traces on inside layer	
PCB trace resistance for 1oz and 2oz Cu	
Package types and dimensions	
PCB parallel plate capacitance	
PCB microstrip capacitance and inductance	
PCB adjacent copper trace capacitance	
PCB via capacitance and inductance	
Common coaxial cable specifications	
Coaxial cable equations	
Resistance per length for different wire types (AWG)	
Maximum current for wire types	
Sensor	
Temperature sensor overview	
Thermistor	
Resistive temperature detectors	
Diode temperature sensors	
Thermocouples	
A/D conversion	
Binary/decimal conversion	
A/D and D/A conversion	
Quantization	
Signal-to-noise ratio	
Total harmonic distortion	
Signal-to-noise ratio	
Effective number of bits	
Noise frequency	
Setting time	